

TOWING SPECIFICATION AND ILLUSTRATION TABLE

Vehicle	Warnings, Notices and Notes	Flatbed		Front and Rear Wheel Lift							
		Flat Bed	Tie Down	Wheel Lift Front	Wheel Lift Rear	Clearance Height — Front	Clearance Height — Rear	Towing from Front	mph — km/h miles - km	Towing from Rear	mph — km/h miles - km
CARS											
Fiesta	A,B,C,I,M,S	1	24	3	5	15 in	15 in	W/Dolly See 25	Unltd	W/Dolly See 25	Unltd
Focus (FWD)	A,B,C,H,I	1	12	3	5	18 in	18 in	W/Dolly See 25	Unltd	W/Dolly See 25	Unltd
Fusion/MKZ (AWD) Fusion/MKZ Hybrid (AWD)	A,B,C,D,E,I	1	22	3	5	19 in	19 in	W/Dolly	Unltd	W/Dolly	Unltd
Fusion/MKZ (FWD) Fusion/MKZ Hybrid (FWD)	A,B,C,E,I	1	22	2	5	19 in	19 in	W/O	Unltd	W/Dolly	Unltd
Fusion Sport (FWD)	A,B,C,E,I,M	1,6,8	22	2	5	19 in	19 in	W/O	Unltd	W/Dolly	Unltd
Taurus/MKS (AWD)	A,B,C,D,E,H,I,M	1	23	3	5	12 in	12 in	W/Dolly	Unltd	W/Dolly	Unltd
Taurus/MKS (FWD)	A,B,C,E,H,I,M	1	23	2	5	12 in	12 in	W/O	Unltd	W/Dolly	Unltd
Mustang (RWD) V6 and V8	A,B,C,D,I,K,L	1	13	3	5	16 in	14 in	W/Dolly	Unltd	W/Dolly	Unltd
Mustang Shelby GT 500 (RWD)	A,B,C,D,I,K,L,M,N	1,7,8,9	13	3	N/A	16 in	14 in	W/Dolly	Unltd	N/A	N/A
Mustang Boss With Side Exhaust (RWD)	A,B,C,D,I,K,L,M,N	1,7,8,9	13	3	N/A	16 in	14 in	W/Dolly	Unltd	N/A	N/A
TRUCKS											
E-Series, E-150/250/350/450	A,B,E,I,O,R	1	14	3	4	12 in	12 in	W/Dolly	Unltd	W/O	Unltd
Edge/MKX (AWD)	A,B,C,D,E,H,I	1	20	3	5	12 in	12 in	W/Dolly	Unltd	W/Dolly	Unltd
Edge/MKX (FWD)	A,B,C,D,E,H,I	1	20	2	5	12 in	12 in	W/O	Unltd	W/Dolly	Unltd
Escape/Escape Hybrid, (4WD)	A,B,C,D,I	1	15	3	5	12 in	12 in	W/Dolly	Unltd	W/Dolly	Unltd
Escape/Escape Hybrid, (FWD)	A,B,C,D,I	1	15	2	5	12 in	12 in	W/O	Unltd	W/Dolly	Unltd
Expedition/Navigator (4WD)	A,B,C,D,G,I,Q,R	1	18	3	5	12 in	12 in	W/Dolly	Unltd	W/Dolly	Unltd
Expedition/Navigator (RWD)	A,B,D,G,I,R	1	18	3	4	12 in	12 in	W/Dolly	* Unltd	W/O	Unltd
Explorer (AWD)	A,B,C,D,E,H,I,M	1	21	3	5	15 in	15 in	W/Dolly	Unltd	W/Dolly	Unltd
Explorer (FWD)	A,B,C,E,H,I,M	1	21	2	5	15 in	15 in	W/O	Unltd	W/Dolly	Unltd
F-150 (4WD)	A,B,C,D,G,I,Q,R	1	18	3	5	12 in	12 in	W/Dolly	Unltd	W/Dolly	Unltd
F-150 (RWD)	A,B,D,G,I,R	1	18	3	4	12 in	12 in	W/Dolly	* Unltd	W/O	Unltd
F-250/350/450/550 (4WD)	A,B,I,J,O,P,Q,R	1,10	16	3	5	12 in	12 in	W/Dolly	Unltd	** W/O	Unltd
F-250/350/450/550 (RWD)	A,B,J,I,O,R	1,10	16	3	4	12 in	12 in	W/Dolly	* Unltd	** W/O	Unltd
Flex/MKT (AWD)	A,B,C,D,E,H,I,M	1	21	3	5	15 in	15 in	W/Dolly	Unltd	W/Dolly	Unltd
Flex/MKT (FWD)	A,B,C,E,H,I,M	1	21	2	5	15 in	15 in	W/O	Unltd	W/Dolly	Unltd
Raptor	A,G,I,R	1	18	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Transit Connect	A,B,C,H,I	1	11	2	5	12 in	12 in	W/O	Unltd	W/Dolly	Unltd
<p>* In case of an emergency, the vehicle can be towed with the drive wheels on the ground up to a speed of 35 mph (55 km/h) and up to a distance of 50 mi (80 km).</p> <p>** On a 4X2/4X4 vehicle in 2HI and the hubs in the AUTO/FREE position, it is acceptable to tow the vehicle with the front wheels on the ground (without dollies) and the rear wheels off the ground.</p>											