



Ford Motor Company Driving Cycle

Description of OBDII Drive Cycle

The following procedure is designed to execute and complete the OBDII monitors and to clear the Ford P1000, I/M readiness code. To complete a specific monitor for repair verification, follow steps 1 through 4, then continue with the step described by the appropriate monitor found under the "OBDII Monitor Exercised" column. When the ambient air temperature is outside 4.4 to 37.8° C (40 to 100° F), or the altitude is above 2438 meters (8000 feet), the EVAP monitor will not run. If the P1000 code must be cleared in these conditions, the PCM must detect them once (twice on some applications) before the EVAP monitor can be "bypassed" and the P1000 cleared. The Evap "bypassing" procedure is described in the following drive cycle.

The OBDII Drive Cycle will be performed using a scan tool. Consult the instruction manual for each described function. NOTE: A detailed description of a Powertrain Control Module (PCM) Reset is found in this section, refer to the table of contents.

Drive Cycle Recommendations:

1. Most OBDII monitors will complete more readily using a "steady foot" driving style during cruise or acceleration modes. Operating the throttle in a "smooth" fashion will minimize the time required for monitor completion.
2. Fuel tank level should be between 1/2 and 3/4 fill with 3/4 fill being the most desirable.
3. The Evaporative Monitor can only operate during the first 30 minutes of engine operation. When executing the procedure for this monitor, stay in part throttle mode and drive in a smooth fashion to minimize "fuel slosh".

WARNING

STRICT OBSERVANCE OF POSTED SPEED LIMITS AND ATTENTION TO DRIVING CONDITIONS ARE MANDATORY WHEN PROCEEDING THROUGH THE FOLLOWING DRIVE CYCLES.

For best results, follow each of the following steps as accurately as possible:

OBDII Monitor Exercised	Drive Cycle Procedure	Purpose of Drive Cycle Procedure
Drive Cycle Preparation	<p>1. Install scan tool. Turn key on with the engine off. Cycle key off, then on. Select appropriate Vehicle & Engine qualifier. Clear all DTC's/ Perform a PCM Reset.</p> <p>2. Begin to monitor the following PIDs: ECT, EVAPDC, FLI (if available) and TP MODE. Start vehicle WITHOUT returning to Key Off.</p>	<p>Bypasses engine soak timer. Resets OBDII Monitor status.</p>

	3. Idle vehicle for 15 seconds. Drive at 64 Km/h (40 MPH) until ECT is at least 76.7°C (170° F).	
Prep for Monitor Entry	4. Is IAT within 4.4 to 37.8°C (40 to 100° F)? If Not, complete the following steps but, note that step 14 will be required to "bypass " the Evap monitor and clear the P1000.	Engine warm-up and provide IAT input to the PCM.
HEGO	5. Cruise at 64 Km/h (40 MPH) for up to 4 minutes.	Executes the HEGO monitor.
EVAP	6. Cruise at 72 to 104 Km/h (45 to 65 MPH) for 10 minutes (avoid sharp turns and hills) Note, to initiate the monitor: TP MODE should =PT, EVAPDC must be >75%, and FLI must be between 15 and 85%	Executes the EVAP Monitor (If IAT is within 4.4 to 37.8° (40 to 100°F))
Catalyst	7. Drive in stop and go traffic conditions. Include five different constant cruise speeds, ranging from 40 to 72 Km/h (25 to 45 MPH) over a 10 minute period.	Executes the Catalyst Monitor.
EGR	8. From a stop, accelerate to 72 Km/h (45 MPH) at 1/2 to 3/4 throttle. Repeat 3 times.	Executes the EGR Monitor.
SEC AIR/CCM (Engine)	9. Bring the vehicle to a stop. Idle with transmission in drive (neutral for M/T) for 2 minutes.	Executes the ISC portion of the CCM.
CCM (Trans)	10. For M/T, accelerate from 0 to 80 Km/h (0 to 50 MPH), continue to step 11. For A/T, from a stop and in overdrive, moderately accelerate to 80 Km/h (50 MPH) and cruise for at least 15 seconds. Stop vehicle and repeat without overdrive to 64 Km/h (40 MPH) cruising for at least 30 seconds. While at 64 Km/h (40 MPH) , activate overdrive and accelerate to 80 Km/h (50 MPH) and cruise for at least 15 seconds. Stop for at least 20 seconds and repeat step 10 five times.	Executes the transmission portion of the CCM.
Misfire & Fuel Monitors	11. From a stop, accelerate to 104 Km/h (65 MPH). Decelerate at closed throttle until 64 Km/h (40 MPH) (no brakes). Repeat this 3 times.	Allows learning for the misfire monitor.
Readiness Check	12. Access the ON-Board System Readiness (OBDII monitor status) function on the scan tool. Determine whether all non-continuous monitors have completed. If not, go to step 13.	Determines if any monitor has not completed.

Pending Code Check and Evap Monitor "Bypass" Check	<p>13. With the scan tool, check for pending codes. Conduct normal repair procedures for any pending code concern. Otherwise, rerun any incomplete monitor.</p> <p>Note: if the EVAP monitor is not complete AND IAT was out of the 4.4 to 37.8° C (40 to 100° F) temperature range in step #4, or the altitude is over 2438 m. (8000 ft.), the Evap "bypass" procedure must be followed.</p> <p>Proceed to step 14.</p>	Determines if a pending code is preventing the clearing of P1000.
Evap Monitor "Bypass"	<p>14. Park vehicle for a minimum of 8 hours. Repeat steps 2 through 12. DO NOT REPEAT STEP 1.</p>	Allow the "bypass" counter to increment to two.

*Reprinted on OBDII web site courtesy of Ford Motor Company
© Ford Motor Company*

[\[OBD-II Home \]](#)

© 2011 B&B Electronics

The OBD-II Home Page is hosted by

