

## SPECIFICATIONS

### Driveline Angles @ Curb Specifications

Engine	Engine Angle (Deg)	Driveshaft Angle (Deg)	Pinion Angle (Deg)
4.0L	3.5	1.8	0.55
4.6L (3V)	2.2	3.9	1.1

All driveshaft and pinion angles point downward.

### General Specifications

Item	Specification
<b>Axle Capacities</b>	
7.5 inch rear axle <sup>a</sup>	1.5 liters (3.0 pints)
8.8 inch rear axle <sup>b</sup>	1.9 liters (4.0/3.75 pints)
Additive Friction Modifier	118 ml (4 oz)
<b>Lubricants</b>	
Motorcraft SAE 75W-140 Premium Rear Axle Lubricant XY-75W140-QL (US); CXY-75W140-1L (Canada) (8.8 inch axle)	WSP-M2C192-A

### General Specifications (Continued)

Item	Specification
Motorcraft SAE 80W90 Premium Rear Axle Lubricant XY-80W90-QL (US); CXY-80W90-1L (Canada) (7.5 inch axle)	WSP-M2C197-A
Additive Friction Modifier XL-3 (US); CXL-3 (Canada)	EST-M2C118-A
Premium Long-Life Grease XG-1-C or XG-1-K (Canada CXG-1-C)	ESA-M1C75-B

- a Service refill capacities are determined by filling the axle 11.1 mm (0.4375 in) to 12.7 mm (0.5 in) below the bottom of the filler hole. The vehicle must be on a level surface.
- b Service refill capacities are determined by filling the axle 25.4 mm (1 in) to 28.6 mm (1.125 in) below the bottom of the filler hole. The vehicle must be on a level surface.