



**C110** (BK)




- (1) -
- (2) 420 (DB/YE)
- (3) -
- (4) -
- (5) 330 (YE/LG)
- (6) 191 (LG/BK)
- (7) 439 (TN/RD)
- (8) 570 (BK/WH)
- (9) 1899 (WH)
- (10) 1715 (RD)
- (11) 208 (GY)
- (12) 1205 (BK)

- (1) 1118 (RD)
- (2) 420 (DB/YE)
- (3) 361 (RD)
- (4) 391 (RD/YE)
- (5) 330 (YE/LG)
- (6) 191 (LG/BK)
- (7) 439 (TN/RD)
- (8) 570 (BK/WH)
- (9) 1899 (WH)
- (10) 1715 (RD)
- (11) 208 (GY)
- (12) 1205 (BK)

**C112** (BK)


**12B637**  
Coil On Plug (COP) 2 (12A366)



Pin	Circuit	Circuit function
1	1118 (RD)	PCM power relay, output
2	1026 (PK/WH)	coil driver (CD) – D control

**C113** (BK)


**12B637**  
Coil On Plug (COP) 3 (12A366)



Pin	Circuit	Circuit function
1	1118 (RD)	PCM power relay, output
2	1028 (WH/PK)	coil driver (CD) – B control

**C111** (BK)


**12B637**  
Coil On Plug (COP) 1 (12A366)



Pin	Circuit	Circuit function
1	1118 (RD)	PCM power relay, output
2	1024 (LG/WH)	coil driver (CD) – A control

**C114** (BK)

**12B637**  
Coil On Plug (COP) 4 (12A366)



Pin	Circuit	Circuit function
1	1118 (RD)	PCM power relay, output
2	1030 (DG/VT)	coil driver (CD) – G control