


Brake Flexible Hose

Material

Item	Specification
High Performance DOT 3 Motor Vehicle Brake Fluid PM-1 (Canada CPM-1)	ESA-M6C25-A

Removal

 **WARNING:** Use of any other than approved DOT 3 motor vehicle brake fluid will cause permanent damage to brake components and will render the brakes inoperative. Failure to follow these instructions may result in personal injury.

 **WARNING:** Carefully read cautionary information on product label. For **EMERGENCY MEDICAL INFORMATION** seek medical advice. In the USA or Canada on Ford/Motorcraft products call: 1-800-959-3673. For additional information, consult the product Material Safety Data Sheet (MSDS) if available. Failure to follow these instructions may result in personal injury.

NOTICE: Brake fluid is harmful to painted and plastic surfaces. If brake fluid is spilled onto a painted or plastic surface, immediately wash it with water.

NOTICE: If equipped with adhesive backed brake pads, do not allow the brake fluid to come in contact with the adhesive backing on the brake pads. If brake fluid is spilled onto the brake pads new pads must be installed.

1. Remove the brake caliper flow bolt and discard the 2 copper washers.
 - To install, tighten to 70 Nm (52 lb-ft).
2. Disconnect the brake line fitting from the brake flexible hose.
 - To install, tighten to 17 Nm (13 lb-ft).
3. Remove the 2 bracket bolts and the brake flexible hose.
 - To install, tighten to 20 Nm (15 lb-ft).
4. To install, reverse the removal procedure.
 - Bleed the brake system. For additional information, refer to [Section 206-00](#).

