

SECTION 414-01 Battery, Mounting and Cables

CONTENTS	PAGE
SPECIFICATIONS	414-01-2

SPECIFICATIONS**Material**

Item	Specification	Fill Capacity
Threadlock and Sealer TA-25	WSK-M2G351-A5	—

General Specifications

Item	Specification
Battery	
Cold Cranking Amps (CCA) measured at -18°C (0°F)	590 CCA
Voltage	12 volts

Torque Specifications

Description	Nm	lb-ft	lb-in
Battery cable harness bracket-to-engine block nut (3.7L)	47	35	—
Battery cable harness-to-valve cover bracket nut (3.7L)	9	—	80
Battery cable harness bracket nut (5.0L, 5.4L)	9	—	80
Battery cable terminal nut	10	—	89
Battery ground cable body terminal bolt	10	—	89
Battery ground cable-to-head terminal bolt (3.7L)	12	—	106
Battery ground cable-to-engine terminal nut (5.0L, 5.4L)	47	35	—
Battery hold-down clamp bolt	8	—	71
Battery tray bolts	11	—	97
Battery Junction Box (BJB) terminal nut	10	—	89
Generator B+ terminal nut	17	—	150
Lower battery cable harness bracket nut (5.4L)	8	—	71
Starter solenoid positive cable terminal nut	12	—	106
Starter solenoid wire terminal nut	5	—	44