

SPECIFICATIONS

General Specifications

Item	Specification
Brake Pads	
Brake pad minimum thickness	3.0 mm (0.118 inch)
Brake pad maximum thickness variation (pad-to-pad)	2.0 mm (0.079 inch)
Brake pad maximum taper wear (in any direction)	3.0 mm (0.118 inch)
Brake Disc	
Front brake disc minimum thickness	28.4 mm (1.11 in)
Rear brake disc minimum thickness	17.4 mm (0.68 in)
Minimum thickness to machine front brake disc	29 mm (1.14 in)
Minimum thickness to machine rear brake disc	18 mm (0.71 in)

General Specifications (Continued)

Item	Specification
Lubricant	
High Performance DOT 3 Motor Vehicle Brake Fluid PM-1 (Canada CPM-1)	ESA-M6C25-A
High Temperature Nickel Anti-Seize Lubricant XL-2	ESE-M12A4-A
Silicone Brake Caliper Grease and Dielectric Compound XG-3-A	ESE-M1C171-A
Brake Parts Cleaner PM-4	—

Torque Specifications

Description	Nm	lb-ft	lb-in
Brake caliper bleeder screw	10	—	89
Brake caliper bolts	33	24	—
Master cylinder brake tube fittings	17	13	—