

SPECIFICATIONS

General Specifications

Item	Specification
Brake Pads	
Minimum brake pad thickness	3.0 mm (0.118 in)
Maximum brake pad thickness variation (pad-to-pad)	2.0 mm (0.079 in)
Maximum brake pad taper wear (in any direction)	3.0 mm (0.118 in)
Brake Disc	
Minimum brake disc thickness	28.4 mm (1.11 in)
Minimum thickness to machine brake disc	29.0 mm (1.14 in)
Lubricant	
High Performance DOT 3 Motor Vehicle Brake Fluid PM-1 (Canada CPM-1)	ESA-M6C25-A or WSS-M6C62-A

General Specifications (Continued)

Item	Specification
High Temperature Nickel Anti-Seize Lubricant XL-2	ESE-M12A4-A
Silicone Brake Caliper Grease and Dielectric Compound XG-3-A	ESE-M1C171-A
Metal Brake Parts Cleaner PM-4 (Canada CPM-4)	—

Torque Specifications

Description	Nm	lb-ft	lb-in
Bleeder screw	10	—	89
Brake caliper anchor plate bolts	115	85	—
Brake caliper bolts	34	25	—
Brake caliper flow bolt	70	52	—
Brake disc shield bolts	20	15	—
Brake hose bracket bolts	20	15	—
Brake tube fittings	17	13	—