

SPECIFICATIONS

General Specifications

| Item | Specification |
|--|-------------------|
| Brake Pads | |
| Brake pad minimum thickness | 3.0 mm (0.118 in) |
| Brake pad maximum thickness variation (pad-to-pad) | 2.0 mm (0.079 in) |
| Brake pad maximum taper wear (in any direction) | 3.0 mm (0.118 in) |
| Brake Disc | |
| Rear brake disc minimum thickness | 17.4 mm (0.68 in) |
| Minimum thickness to machine rear brake disc | 18.0 mm (0.7 in) |
| Lubricant | |
| High Performance DOT 3 Motor Vehicle Brake Fluid PM-1 (Canada CPM-1) | ESA-M6C25-A |
| High Temperature Nickel Anti-Seize Lubricant XL-2 | ESE-M12A4-A |

General Specifications (Continued)

| Item | Specification |
|--|---------------|
| Silicone Brake Caliper Grease and Dielectric Compound XG-3-A | ESE-M1C171-A |
| Brake Parts Cleaner PM-4 | — |

Torque Specifications

| Description | Nm | lb-ft | lb-in |
|-------------------------------------|-----|-------|-------|
| Anti-moan bracket U-bolt nuts | 35 | 26 | — |
| Bleeder screw | 10 | — | 89 |
| Brake caliper flow bolt | 70 | 52 | — |
| Brake disc shield bolts | 20 | 15 | — |
| Brake caliper anchor plate bolts | 103 | 76 | — |
| Brake flexible hose bracket bolts | 20 | 15 | — |
| Brake caliper bolts | 33 | 24 | — |
| Brake line fitting | 17 | 13 | — |
| Brake caliper support bracket bolts | 68 | 50 | — |